# **SLD-31**

## 31" Carbon Fiber Camera Slider

## **ONE SHEET**

## **Overview**

The Ikan 31" Carbon Fiber Slider is a smooth lightweight slider that supports cameras up to 12lbs and offers a full 26 inches of precise linear travel. The camera platform rides on 4 rollers that are captive on the carbon fiber rods and the slider may be used inverted or vertically as well as horizontally. The outrigger legs can spin 360 degrees for different mounting and the rubber feet can adjust to level.



**SLD-31** | 31" Carbon Fiber Slider | **UPC Code:** 847983014897

## **Special Features**

- Ball-bearing Slider System
- Lightweight Carbon Fiber
- Rail Size: 19 mm
- Actual travel: 26" (66 cm)
- 8 Sealed Bearings
- Adjustable Outrigger Feet
- Padded carrying case



## **Recommended For**

- Location/Studio Cinematography
- Time lapse Shooting
- Cinematic Dolly Moves



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



#### **Smooth-Sealed Bearing Movement**

The SLD-31 comes equipped with eight sealedbearing rollers to ensure smooth travel. Even when being used over rough terrain.

#### **Excellent Moves for Smaller Rigs**

With 26" of travel, and up to 12 lbs weight capacity, this slider to great for on-the-go shooting.

#### **Adjustable Feet**

The slider includes individually adjustable outrigger feet to be able to work in multiple different kinds of terrain.

#### **Center & Side Support Mounting**

Slider is equipped with a center 1/4"-20 and 3/8"-16 thread mount, and two 1/4"-20 stand mounts on each end.

#### Lightweight & Portable

At 2.5 lbs, this lightweight slider packs light, and includes a padded carry case.

#### **Integrated Bubble-Level**

Integrated bubble-level makes it easy to ensure your shot is level.

#### What's Included

- 1 x 31" Carbon Fiber Slider
- 1 x Padded Carry Case
- 4 x Adjustable Rubber Feet

### Features you need, Prices you want.

Specifications	
Height	1.9 ln. / 5 cm
Length	31 ln. / 80 cm
Width	7.8 ln. / 20 cm
Net Weight	1.5 lbs / 600 gm
Gross Weight	5 lbs
Packaging Dimensions	36 x 8 x 5.25 ln.
Supported Camera Weight	18 lbs / 8 kg
Travel Length	26 ln. / 66 cm
Mounting Point	3/8"-16 Mounting Point
Carriage Lock	Friction Lock Knob
Construction	Carbon Fiber, Machined Aluminum, Rubber Feet
Shipping Dimensions	36 x 8 x 5.25 ln / 914 x 203 x 133 mm
Shipping Weight	5 lbs / 2.2 kg

#### **Optional Accessories**



IK-RSR3 3" Camera Riser



**IK-RSR6**6" Hi-Hat Riser



IK-RSRS
6" Camera Riser
Hi-Hat with Swivel



100BF 100mm Ball to Flat Adapter



**75BF**75mm Ball to
Flat Adapter



GH03F Flat Base Pro Fluid Head 11 lbs Max





