



Saga 7" Super High Bright HDMI/3G-SDI On-Camera Field Monitor with 3D-LUTs and Scopes UPC: 8479830

Overview

The Ikan Saga line of LCD monitors is designed to help you tell your story. The 7" super bright SX7 is designed with high end features, durability, and field use in mind. The SX7 is viewable in even the brightest conditions with its super bright 1700 nit LCD panel. With the aluminum chassis and gorilla glass, the SX7 is able to survive any production shoot. The monitor's high end software features such as scopes and 3D-LUTs help you get the right shot the first time.

Specifications	
Aspect Ratio	16 x 10
Backlight	LED
Brightness	2000 cd/m2
Build Material	Heavy Duty Plastic
Color Depth	16.7 Million
Color System	PAL / NTSC / SECAM (Auto-Detected)
Contrast Ratio	1200:1
Dimensions	8.5 x 5.7 x 0.9 in.
Input Voltage	DC 7V-24V
Inputs	HDMI, 3G-SDI
Operating Temperature	32°F~122°F (0°C~50°C)
Outputs	HDMI, 3G-SDI
Pixel Pitch	0.07875 x 0.07875 mm
Power Consumption	
Resolution	1920 x 1200
Response Time	20ms
Screen Size	7 inch
Viewing Angle	178° horizontal / 178° vertical
Weight	2 lbs

Supported Video Signals Specifications		
3G-SDI	2048x1080psf @ 23.98, 24, 25, 29.97, 30 Hz 1920x1080p @ 50, 59.94, 60 Hz (4:2:2 YCBCR)	
HD-SDI	1280x720p @ 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 Hz (4:4:4 YCBCR) 1920x1080i @ 50, 59.94, 60 Hz (4:4:4 YCBCR) 1920x1080psf @ 23.98, 24, 25, 29.97, 30 Hz (4:4:4 YCBCR) 1920x1080p @ 23.97, 24, 25, 29.97, 30 Hz (4:4:4 YCBCR)	
SD-SDI	720x480i @ 60Hz (4:2:2) 720x576i @ 50Hz (4:2:2)	
HDMI	720x480i @ 60 Hz 720x576i @ 50 Hz 1280x720p @ 23.97, 24, 25, 29.94, 30, 50, 59.94, 60 Hz 1920x1080i @ 50, 59.94, 60 Hz 1920x1080psf @ 24, 25, 29.97, 30 Hz 1920x1080p @ 23.98, 24, 25, 29.97, 30, 50, 59.94, 60Hz	





Special Features

- 2000 nit super high bright LCD panel
- 1920 x 1200 full HD plus LCD panel
- Custom 3D-LUT support
- 3G-SDI / HDMI Inputs and Outputs
- · Waveform, vectorscope, RGB parade, histogram
- · Peaking, false color, clip guides, and viewing angles

What's Included

1 x Saga X7 Monitor

1 x V-Mount Plate (Attached)

1 x Mini-XLR to P-TAP Cable

1 x Dual Sony "L" Battery Adapter

1 x Hard Case

Optional Accessories

C-1K Battery Charger (BP-U, V-Mount & Anton Bauer)

IB-L95 IB-L95 / 95Wh Professional Battery
IBS-970 Sony L-Series NP-F970 Compatible

IBS-970 Sony L-Series NP-F970 Compatible Battery
ICH-KDUAL-L Dual Charger for Sony L-Series Style Batteries

MA207 7 Inch Articulating ArmMA211 11 Inch Articulating Arm







