



7" HDMI LCD Monitor with IPS Panel

ONE SHEET

Overview

The VH7i Sets a new standard for cost and performance. Its thin profile and lightweight make it an ideal solution for many types of productions. With its great viewing angles and color reproduction, will help you always get the best shot. Software features such as False color, Peaking, and Clip guides will help you get accurate color and exposure. The VH7i supports ikan's BP5 interchangeable battery plates so no matter which battery system you are invested you will be covered.



VH7i-1 | 7" HDMI LCD Monitor with IPS Panel | **UPC Code:** 847983013494

VH7i-2 | 7" HDMI LCD Monitor with IPS Panel | **UPC Code:** 847983013500

Special Features

- 1280 x 800 High Quality IPS Panel
- HDMI Input & Output
- Thin & Lightweight
- False Color, Peaking & Clip Guides

Recommended For

- Field Use
- On-Camera Use



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

VH7i-1

Features you need, Prices you want.

Features

Itament facillam eum nimagnihil il molupidesse voluptia nienisciist es eati ma ad et, cusapis eate con rae estempor se nossit alibusamus vero quas solupta dolor aut aditati dicit blacepe et ommodias simenda dis enes renda que laborum core nobitat quatibusam

Features

Onsequae ma consequis utaquas nita doluptati ipidelessin es ellum fugitaerume voluptinum facepedi tem fugiaerem corecae. Beaquos eum nus quam fuga. Ento occur apienda nihit, sequam rest, odictori optatati natus dipsus.

Features

It arum nonempossus alibus. Faccum et, netur, vit etur rercis simus, soluptiur aut aborrioriore nonseque consequi seditatur sim ipit volutatatis et la plati te nobitia sa que es et ut vel idesedist, sitiscitis sim fuga. Xim laut eum ent.

What's Included

- 1 x VH7i Monitor
- 1 x AC Adapter
- 1 x Sunhood
- 1 x Canon 900, Sony L, Panasonic D54 Battery Plates
- 1 x SM-103

Product Specs

Aspect Ratio	16:10
Brightness	400 cd/m2
Build Material	Plastic
Built-In Speaker	PAL / NTSC / SECAM
Color System	7"
Contrast Ratio	7.36" x 5.6" x 1.3"
Dimensions	IPS
Display Technology	DC 6v -24v
Input Voltage	3G-SDI, HDMI, Component, Composite
Operating Temperature	3G-SDI, HDMI, Component, Composite
Pixel Pitch	0.11775 x 0.11775 (mm)
Power Consumption	11 Watts
Resolution	1280 x 800
Response Time	30 ms
Screen Size	170° (H) 170° (V)
Viewing Angle	1 lb
Weight	3 lbs
Shipping Weight	3.1" x 14.75" x 7.75"

Supported Video Signals

HDMI	720 x 480i & 720x 48p @ 59.94, 60 Hz
	720 x 576i & 720 x 576i @ 50 Hz
	1280 x 720p @ 50, 59.94, 60 Hz
	1920 x 1080i @ 50, 59.94, 60 Hz
	1920 x 1080psf @ 24, 25, 29.97, 30 Hz
	1920 x 1080p @ 23.97, 24, 25, 29.94, 30, 50, 59.94, 60 Hz

Optional Accessories

- MA207 7" Articulating Arm
- MA211 11" Articulating Arm
- IBC-950G Canon Compatible Battery
- IBC-988 ikan's Canon "900" Series Style Ultra-High Capacity Battery
- IBC-E6+ Canon LP-E6 Compatible Battery
- IBN-EL15 Nikon EN-EL15 Compatible
- IBP-D54 Panasonic Compatible Battery
- IBP-D88 ikan's Panasonic "D54" Type Ultra-High Capacity Battery
- IBS-1170 Sony "L" Series Compatible Ultra-High Capacity Battery
- IBS-970 Sony "L" Series NP-F970 Compatible Battery
- IBS-750 Sony "L" Series NP-F750 Compatible Battery
- HDMI-AA-18 1.5' HDMI Cable 1.4v (Standard to Standard)
- HDMI-AC-18 1.5' HDMI Cable 1.4v (Mini to Standard)
- HDMI-AD-18 1.5' HDMI Cable 1.4v (Micro to Standard)

