

# 5" HDMI Monitor w/ Sunhood & E6 Battery Plate

## **ONE SHEET**

### **Overview**

Slim, lightweight and affordable, the VL5e is a 5" ultra-portable, on-camera monitor. Its slender build allows it to fit in any camera bag and, at less than half a pound, is ideal for handheld rigs. But don't mistake its compact size for lack of capacity — it has tons of software features to help you get the images you want.



VL5e | 5" HDMI Monitor w/ Sunhood & E6 Battery Plate | UPC Code: 847983014910

# **Special Features**

- Resolution of 800x480
- HDMI Input & Output
- Histogram
- Peaking, False Color, & Clip Guides
- Headphone Output

# **Recommended For**

- Field Production
- Studio Use
- On-Camera Use



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp





#### Small in Size, Big on Value

Size makes the VL5e ideal for any type of mobile production—perfect for gimbals, handheld rigs, or shoulder rigs. To assist with those outdoor shoots, a sun visor and full sunhood are included.

#### **Software Features**

Check exposures using false color, clip guides and histogram. Peaking and pixel-to-pixel help ensure that focus is where you want it. Frame guides and DSLR Scaling enhance your ability to capture the image you seek. Plus, you can map your most-used features to four easily accessed function buttons.

#### **Hardware Features**

The VL5e is equipped with an HDMI input & output. You can also check audio via the headphone port. The monitor uses Ikan BP5-style battery plates that are compatible with seven different power options. The VL5e also features a full-size USB port for software updates as well as powering other 5V devices.

#### What's Included

- 1 x VL5e Monitor
- 1 x 12V AC Adapter
- 1 x Battery Adapter Plate\*
- \*For Sony, Canon Or Panasonic
- 1 x Shoemount
- 1 x Sun Visor

#### **Optional Accessories**

IBC-950GCanon Compatible BatteryIBC-E6+Canon LP-E6 Compatible BatteryIBP-D54Panasonic Compatible BatteryIBS-970Sony L-Series Compatible BatteryHDMI-2-HDMISingle Input / Dual Output Passive

**HDMI Splitter** 

### Features you need, Prices you want.

Product Specs	
Backlight	LED
Color Arrangement	RGB - Stripe
Contrast Ratio	600:1
Diagonal (Inch)	5 ln.
Dimensions	3.5 x 5.2 x 0.6 ln.
Inputs	HDMI
LCD Brightness	400 cd/m2
Operating Volts	DC 5-16v
Outputs	HDMI
Power Consumption	4.2 Watt
Resolution	800 x 480
Viewing Angle	150°(H) / 130°(V)
Weight	0.33 lbs
Shipping Dimensions	3.5 x 7.5 x 6.2 ln.
Shipping Weight	2 lbs

Supported Video Signals	
HDMI	720x480i & 720x480p @ 59.94, 60 Hz
	720x576i & 720x576p @ 50 Hz
	1280x720p @ 50, 59.94, 60 Hz
	1920x1080i @ 50, 59.94, 60 Hz
	1920x1080psf @ 24, 25, 29.97, 30 Hz
	1920x1080p @ 23.97, 24, 25, 29.94, 30, 50, 59.94, 60 Hz





