

C-2KIT-95S

Dual Pro Battery Charger w/ 2x 95Wh V-Mount Batteries



What's included

- 2 x IB-L95S
- 1 x C-2KS

Checked by

CONDITIONS OF WARRANTY SERVICE

- Free service for one year from the day of purchase if the problem is caused by manufacturing errors.
- The components and maintenance service fee will be charged if the warranty period has expired.

Free Service will not be Provided in the Following Situations: (* Even if the product is still within the warranty period.)

- Damage caused by abuse or misuse, dismantling, or changes to the product not made by the company.
- Damage caused by natural disaster, abnormal voltage, and environmental factors etc.

C-2KIT-95S

Dual Pro Battery Charger w/ 2x 95Wh V-Mount Batteries



SPECIFICATIONS

- Amp Hours: 8
- Battery Bays: 95 Wh/ 6.6 Ah
- Chemistry: Lithium-Ion
- Connection: Gold Mount
- Dimensions: 5.6x3.4x2 In.
- Output Voltage: 14.8V DC
- Watt Hours: 95
- Weight: 1.5 lbs

FEATURES

- Compact Form Factor
- Compatible with V-Mount
- LED Display Indicates Battery Capacity and Real-Time Run Time
- 2-Pin Power Tap for 12V Accessories

CAUTION

- Use and store the battery in place with temperatures of -4° to 131° F and less than 85% humidity.
- Keep battery away from fire or heat. Do not incinerate. Exposure of battery to extreme heat may result in an explosion.
- Avoid high pressure.
- Do not short-circuit. A short-circuit may cause severe damage to the battery.
- Do not expose the battery to moisture or rain.
- Do not drop, hit or otherwise abuse the battery as this may result in the exposure of the cell contents, which are corrosive.
- Remove from the device and stored in a cool, dry, clean place if the battery will not be in use for a month or longer.
- Use recommended charger, ikan C-2KA Battery Charger.
- Do not remove the battery from camera when the camera is on.
- Battery should be charged up to 50% of full power for long term storage.

ikan

www.ikancorp.com


713-272-8822

C-2KIT-95S

Dual Pro Battery Charger w/ 2x 95Wh V-Mount Batteries



Figure 1



C-2KS Specifications

Dimensions: 4.57 x 8.86 x 5.51 In.

Input AC: 90~242V AC, 47~63Hz

Mount: Sony V-Mount

Weight: 2.18 lbs

C-2KS Features

- Charging 2 Batteries at once
- Charging Power Indicators
- XLR 4-Pin 12V DC Output
- Built-In Intelligent Management
- Capacity Management Circuit
- Charge Time Less than 4 Hours
- Conductive Gold Connections
- Extended Legs for Stabilizing

ikan

www.ikancorp.com

713-272-8822