

LS-1200TE

1200 Watt HMI Fresnel Kit (*Lightstar*)

ONE SHEET

Overview

The Lightstar 1200 Watt HMI Fresnel Kit provides the powerful light you need when the sun isn't working in your favor. From spot to flood lighting, it delivers all of the daylight control at your fingertips. The kit's heavy-duty aluminum alloy fixture allows heat to dissipate quickly. The fresnel lens lets you control the spread of the light easily while on-board dimming adjusts the level of brightness.

No matter how demanding the type of environment, the 8-meter long Head to Ballast cable consists of heavy-duty coating and industrial connectors to withstand the elements. The ballast itself is much smaller and lighter than standard versions. To top it off, its 575/1200 Watts provide flicker-free shooting up to 10,000 FPS!



LS-1200TE | 1200Watt HMI Fresnel Kit (*Lightstar*) | UPC Code: 8479830

Special Features

- Aluminum alloy light fixture
- Efficient Beam Output with glass Fresnel lens
- 8 meter Head to Ballast cable
- 575 watt/1200 watt Electronic Ballast

Recommended For

- Studio Lighting
- Field Lighting
- Specialty Lighting

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

LS-1200TE

Features you need, Prices you want.

Aluminum Alloy Design

The LS-1200TE light features a heavy-duty aluminum body for quick heat release.

Efficient Beam Output

The fresnel lens makes it easy to create a clean, sharp edge through the beam.

8-Meter Head to Ballast Cable

The ballast cable's heavy-duty construction allows you to place the light far away from the ballast.

575/1200W Electronic Ballast

The electronic ballast's 575/1200W provides flicker-free shooting at very high frame rates.

What's Included

- 1 x 1200W HMI Fresnel Light Fixture
- 1 x Barn Doors
- 1 x 575/1200W Electronic Ballast
- 1 x 8 meter Head to Ballast Cable
- 1 x Yoke
- 1 x Gel Holder

Specs

Head Type	LS-1200TE
Rating	1200 Watt
Light Source	Metal Halide 1200W / SE
Power Supply	Electronic Ballast 575 W
Voltage Range	95V-120V
Lamp Base / Bulb	HMI 1200 / 120V / G38 / MSR 1200 HR
Dimming	50-100%
Lens Size	Fresnel 6.8" Lens
Focusing	Knob Controlled
Beam Angle	6-58
Cooling System	Air-Cooled
Yoke	Cast Aluminum w/ 11/8" Pin
IP Class	IP23
Fixture Size	23 x 16 x 12 In.
Fixture Weight	24.2 lbs
Shipping Dimensions	26 x 18 x 18 In. 66.04 x 45.72 x 45.72 cm
Shipping Weight	59 lbs / 26.7 kg

LS-1200TE Photometrics

	6 Degrees	58 Degrees
13 Ft	46880 LUX	3125 LUX
	4355.2 FC	292.8 FC
16 Ft	20800 LUX	1390 LUX
	1932.3 FC	129.1 FC
19 Ft	11700 LUX	780 LUX
	1086.9 FC	72.4 FC

Accessories

- KCP-703 Stage Clamp w/ 16mm Stud
- SW-04 Safety Wire
- CV600 Chrome Exposure / Spectrometer from UPRtek



ikan

Houston, Texas

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com