

# LS-2500E

2500 Watt HMI Fresnel Kit (*Lightstar*)

ONE SHEET

## Overview

The Lightstar 2500 Watt HMI Fresnel Kit delivers the color of the sun to your fingertips! From spot to flood lighting, it provides all the necessary daylight control. The kit's heavy-duty aluminum alloy fixture allows heat to dissipate quickly. The Fresnel lens lets you control the spread of the light while the on-board dimming feature adjusts the level of brightness. With its durable coating and industrial connectors, the 7 meter long Head to Ballast cable enables it to endure the most demanding environments with ease. The 2500/4000 Watt Electronic Ballast can handle Flicker free shooting up to 10,000 fps. Best of all, it is much smaller and lighter than the standard magnetic ballast!



LS-2500E | 2500 Watt HMI Fresnel Kit (*Lightstar*) | UPC Code: 847983020386

## Special Features

- Aluminum Alloy Light Fixture
- 2500/4000 Watt Electronic Ballast
- 7 Meter Head to Ballast Cable
- Barn Doors Included

## Recommended For

- Studio Lighting
- Field Lighting

ikan

[www.ikancorp.com](http://www.ikancorp.com)

1.713.272.8822

[sales@ikancorp.com](mailto:sales@ikancorp.com)



[www.facebook.com/ikanseit](http://www.facebook.com/ikanseit)



[www.twitter.com/ikancorp](http://www.twitter.com/ikancorp)



[www.vimeo.com/ikancorp](http://www.vimeo.com/ikancorp)



[www.youtube.com/ikancorp](http://www.youtube.com/ikancorp)

# LS-2500E

Features you need, Prices you want.

## Aluminum Alloy Design

The heat fixture features a heavy-duty aluminum body for quick heat release.

## Efficient Beam Output

The fresnel lens makes it easy to create a clean, sharp edge through the beam.

## Powerful Electronic Ballast

The 2500/4000 Watt Electronic Ballast provides flicker-free shooting up to 10,000 fps.

## Head to Ballast Cable

The heavy-duty 7 meter ballast cable extends far enough for you to place the light away from the ballast.

## Increase Bulb Life

The 2500/4000 Watt Electronic Ballast increases bulb life by at least 20% when compared to a magnetic ballast.

## What's Included

- 1 x 2500/4000 Watt Electronic Ballast
- 1 x 2500W HMI Fresnel Light Fixture
- 1 x 7 Meter Head to Ballast Cable
- 1 x Barn Doors
- 1 x Gel Holder
- 1 x Yoke

## LS-2500E Fixture Specifications

|                 |                               |
|-----------------|-------------------------------|
| Head Type       | HMI Fresnel 2500W             |
| Lens Size       | Fresnel 9.8" lens             |
| Lamp Base       | 2500W / 115V / G38            |
| Beam Angle      | 7°-60°                        |
| Control/Dimming | 50%-100%                      |
| Focusing        | Knob Controlled               |
| Build Material  | Aluminum                      |
| Cooling System  | Air Cooled                    |
| Yoke            | Cast Aluminum with 1 1/8" Pin |
| IP Class        | IP23                          |
| Fixture Size    | 29 x 20.3 x 15.6 in.          |
| Fixture Weight  | 43 lbs                        |

## Electronic Ballast Specifications

|                           |                               |
|---------------------------|-------------------------------|
| Power Supply              | Electronic Ballast 2500/4000W |
| Input Voltage             | 24VDC/100-240VAC              |
| Electronic Ballast Size   | 17.7 x 10.2 x 14.2 in.        |
| Electronic Ballast Weight | 43.7 lbs                      |

## Shipping Specifications Box 1

|                           |                  |
|---------------------------|------------------|
| Shipping Dimensions Box 1 | 20 x 18 x 21 in. |
| Shipping Dimensions Box 2 | 22 x 15 x 20 in. |
| Shipping Weight           | 92 lbs           |

## Optional Accessories

KCP-703  
SW-04

Stage Clamp with 16mm Stud  
Safety Wire

