

# LS-575PE

575 Watt HMI Par Kit (*Lightstar*)

ONE SHEET

## Overview

Crisp, clear, and balanced Daylight light is achievable with the Lightstar 575 Watt HMI Par Kit. A hot light won't be an issue as the aluminum alloy chassee provides quick heat release.

The light kit features an 8-meter ballast cable, which easily attaches from the fixture to the ballast. It also comes with a five lens set that you can focus in any direction to create the best shot. The included barn door top off this great lighting package to equip you for any lighting production!



LS-575PE | 575 Watt HMI Par Kit (*Lightstar*) | UPC Code: 847983015122

## Special Features

- Aluminum Alloy Light Fixture
- 575 Watt/1200 Watt Electronic Ballast
- 8-Meter Head to Ballast Cable
- 5 Lens set for Spot, Narrow Flood, Flood, Super Flood, & Frost
- Barn Doors Included

## Recommended For

- Studio Lighting
- Field Lighting
- Specialty Lighting

ikan

[www.ikancorp.com](http://www.ikancorp.com)

1.713.272.8822

[sales@ikancorp.com](mailto:sales@ikancorp.com)



[www.facebook.com/ikanseit](http://www.facebook.com/ikanseit)



[www.twitter.com/ikancorp](http://www.twitter.com/ikancorp)



[www.vimeo.com/ikancorp](http://www.vimeo.com/ikancorp)



[www.youtube.com/ikancorp](http://www.youtube.com/ikancorp)

# LS-575PE

Features you need, Prices you want.

## Aluminum Alloy Fixture

The heavy-duty aluminum alloy light fixture enables heat to dissipate much faster.

## Powerful Electronic Ballast

The 575/1200W Electronic Ballast provides flicker-free shooting at extremely high rates.

## Head to Ballast Cable

The heavy-duty 8-Meter ballast cable extends far enough for you to place the light away from the ballast.

## 5 Lens Set

The five lens set provides all the control you will need for any Par light. It includes these different types:

- Spot
- Flood
- Narrow Flood
- Super Flood
- Frost

## Barn Doors Included

The large barn doors allow you to easily shape and cut the light as needed.

## What's Included

- 1 x 575W HMI PAR Light Fixture
- 1 x Barn Doors
- 1 x 575/1200 Electronic Ballast
- 1 x 8 Meter Head Cable to Ballast
- 1 x Yoke
- 1 x Gel Holder
- 1 x 5 Insert Lens System

## Specs

Head Type	HMI PAR 575W
Rating	575 Watt
Light Source	575 Watt
Power Supply	Electronic Ballast 575/1200 Watt
Voltage Range	95V-120V
Lamp Base / Bulb	HMI 575 / 120V / G22
Dimming	50-100%
Lens Size	195 mm / 7.6"
Focusing	5 Insert Lens System
No Lens	5°
Spot Beam Angle	9°
Narrow Flood Angle	11° x 22°
Flood Beam Angle	21° x 42°
Super Flood Beam Angle	42°
Frost Beam Angle	35°
Cooling System	Air Cooled
Yoke	Cast Aluminum w/ 1 1/8" Pin
IP Class	IP23
Fixture Size	18.5 x 10.5 x 12.5 In.
Fixture Weight	18 lbs
Shipping Dimensions	24 x 20 x 12 In. 60.06 x 50.8 x 30.48 cm
Shipping Weight	41 lbs / 18.5 kg

## Accessories

- KCP-703** Stage Clamp w/ 16mm Stud
- SW-04** Safety Wire
- CV600** Chrome Exposure / Spectrometer from UPRtek

