

LW-3F2H

Lyra Daylight 5-Point LED Soft Panel Light Kit w/ 3x LW10 + 2x LW5

ONE SHEET

Overview

Ikan introduces the new brand of Lyra Soft Lights. What you can expect when high CRI LED chips combine with a soft panel is a beautiful, soft wrapping light. What's unique about a Lyra soft light is how it creates a nice, clean shadow. The Lyra Daylight Soft Panel Half x 1 LED Light is equivalent to a 350-Watt incandescent soft light.

Among its features include a 5600K color temperature, which delivers stunning high fidelity. The 110° wide beam angle can easily light a large area by itself. The 30° yoke, the Baby 5/8" & Junior 1-1/8" combo pin also allow you to configure or attach them to any stand. Additionally, the yoke's strong steel tension knobs can securely lock the light in place at any angle.

On the back, the large yellow control knob lets you adjust the light's brightness with just a few simple clicks! The LED readout provides extremely precise measurements for reference. Battery flexibility is guaranteed with Gold & V-Mount pro battery plates included. You can also plug in the Lyra Soft Light practically anywhere thanks to its maximum 40-Watts at 0.3 amps.

Add to that Ikan's reliable barn doors with intensifiers and you can clearly see why Lyra's Soft Lights are the best value package!



LW-3F2H | Lyra Daylight 5-Point LED Soft Panel Light Kit w/ 3x LW10 + 2x LW5 | UPC Code: 847983018390

Special Features

- High CRI Chip LEDs paired with 1/2 stop soft diffusion panel
- Solid 5600K Color Temperature
- Bright consistent light
- Beam Angle: 110 degrees
- Clean single shadow without artifacts
- Baby 5/8 inch/Junior 1-1/8 Combo Pin adapter with right angle receiver hole
- 30 degree angled yoke for unobstructed movement

Recommended For

- Studio Lighting
- Field Lighting

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

LW-3F2H

Features you need, Prices you want.

High Soft Light Combination

The high CRI LED chips and 1/2-Stop soft diffusion panel can output a strong, bright diffused light.

Consistent 5600K Temperature

The Lyra Soft Light's 5600K color temperature delivers a consistently bright light at all times.

Consistent & Bright

The Lyra Soft Light is ideal for quick interviews; the bright light won't overheat your talent or waste your time.

110° Beam Angle

The Lyra Daylight's wide beam angle provides a large amount of soft light all on its own.

Clean Single Shadow

Lyra's Soft Lights create single shadows that produce more of a natural, clean shot.

Versatile Combo Pin

The Baby 5/8" and Junior 1-1/8" combo pin adapter makes it easy to attach to any grip stand.

30° Angled Yoke

The 30° yoke provides unobstructed movement of the light.

Steel Tension Knobs

The new steel tension knobs are built to be stronger and more secure. This allows you to lock the light in at any angle.

Single Knob Control

A single control knob makes it easy to adjust brightness at any time.

LED Readout

The new, brighter LED readout provides precise adjustments of light output.

AB & V-Mount

Battery flexibility is key when you're on-the-go.

Barndoors Included

Ikan's reliable barndoors with intensifiers make it much easier to shape the light as needed.

Maximum Power Draw

The Lyra soft light has a maximum power draw of 40-Watts, which allows you to plug into any AC Power.

350-Watt Equivalent

By comparison, the Lyra Daylight Soft Panel Half x 1 LED Light is equivalent to a 350-Watt incandescent soft light.

RF Remote Control

Controlling multiple lights at a distance is possible with the RF remote control.

LW5 Specs

Light Source	255 0.2 Watt LEDs
Head Type	Daylight 5600K
Lens	1/2 Stop Soft Diffusion
Beam Angle	110°
Control / Dimming	Knob Control
Build Material	Heavy Duty Resin Plastic
Cooling System	Passive Cooling
Stand Mount	Baby 5/8" & Junior 1-1/8" combo pin
Fixture Size	14 x 8 x 3 In.
Fixture Weight	4 lbs
Power Supply	Input: 110-220 VAC Output: 15VDC
Yoke	30°

LW10 Specs

Light Source	450 0.2 Watt LEDs
Head Type	Daylight 5600K
Lens	1/2 Stop Soft Diffusion
Beam Angle	110°
Control / Dimming	Knob Control
Build Material	Heavy Duty Resin Plastic
Cooling System	Passive Cooling
Stand Mount	Baby 5/8" & Junior 1-1/8" combo pin
Fixture Size	14 x 14 x 3 In.
Fixture Weight	6 lbs
Power Supply	Input: 110-220 VAC Output: 15VDC
Yoke	30°

Shipping

Shipping Dimensions (Box 1)	22 x 18 x 16 In.
Shipping Weight (Box 1)	24 lbs
Shipping Dimensions (Box 2)	24 x 20 x 20 In.
Shipping Weight (Box 2)	41 lbs
Shipping Dimensions (Box 3)	41 x 9 x 9 In.
Shipping Weight (Box 3)	14 lbs
Shipping Dimensions (Box 4)	41 x 9 x 9 In.
Shipping Weight (Box 4)	16 lbs

What's Included

- 2 x Half x 1 Light Fixture
- 2 x Light Bag
- 2 x Stand Bag
- 3 x 1 x 1 Light Fixture
- 5 x Gold Mount Battery Plate
- 5 x HD Light Stand
- 5 x Power Supply w/ Cable
- 5 x Remote Control
- 5 x V-Mount Battery Plate
- 5 x Yoke Mount
- 5 x Safety Chain

