

# MW8-3PT-KIT

Kit with 3 x Mylo Daylight Half x 1 LED Light

ONE SHEET

## Overview

Ikan's Mylo MW8 LED light offers a wide variety of lighting options within a compact package for cinematographers. The high 95+ CRI LED lenses provide high color fidelity with a consistent brightness from/between 10-100%! The 50-degree beam angle makes it easy to light a large area with just one fixture. The Mylo MW8 Daylight LED Half x 1 light is equivalent to a 750-watt incandescent light.

Durability and versatility are key features of this impressive LED light. The heavy duty metal chassis allows it to endure any harsh field environment while the strong, steel tension knobs on the yoke securely lock the light in place at all times. The Baby 5/8" and Junior 1 1/8" combo pin also allow you to attach or configure it to any grip stand. As for battery power, an AC power supply and two Sony "L" series batteries for DC power come with this incredible light package!

On the back, the large yellow button/knob allows you to adjust the light's brightness with a few simple clicks. Ikan's reliable barn doors with intensifiers are included to shape the light as needed. The LED readout also provides very precise measurements. With a maximum power draw of 50W at 120V, the Mylo MW8 Daylight 5600K LED Half x 1 light can plug into (just about) any outlet!



MW8-3PT-KIT | Kit with 3x Mylo Daylight Half x 1 LED Light | UPC Code: 847983020485

## Special Features

- 95+ CRI LEDs
- 5600K Color Temperature
- Bright, consistent light
- 50° Beam Angle
- Baby 5/8 Inch and Junior 1-1/8 Inch Combo Pin adapter with right angle receiver hole
- Strong Steel tension knobs for locking the light into place
- Heavy Duty metal chassis
- Single knob control for adjusting color or brightness.

## Recommended For

- Studio Lighting
- Field Lighting

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com



[www.facebook.com/ikanseeit](http://www.facebook.com/ikanseeit)



[www.twitter.com/ikancorp](http://www.twitter.com/ikancorp)



[www.vimeo.com/ikancorp](http://www.vimeo.com/ikancorp)



[www.youtube.com/ikancorp](http://www.youtube.com/ikancorp)

# MW8-3PT-KIT

Features you need, Prices you want.

## 95+ CRI LEDs

With more than 800 95+ LED lenses, the Mylo MW8 Light provides incredible color rendition and brightness.

## Consistent 5600K Temperature

The Mylo MW8 LED Light delivers a consistently solid 5600K color temperature ranging between 10-100% brightness.

## Consistently Bright

Consistent, bright lighting is what you can expect from the MW8 Daylight Half x 1 LED Light.

## 50° Angle

A tight, 50° beam angle offers bright lighting for both short and long distances.

## Combo Pin Adapter

The Baby 5/8 Inch and Junior 1-1/8 Inch combo pin includes a right angle receiver hole to quickly and easily attach it to any grip stand.

## Steel Tension Knobs

The new, stronger steel tension knobs securely lock the light in place at any angle.

## Reliable Durability

The heavy duty metal chassis enables you to use the light in any shooting environment without risk of damage.

## Single Knob Control

A single knob control makes it easy to adjust the light's brightness with a few simple clicks!

## New LED Readout

The new LED readout is brighter and provides a quick reference of the light output with precise measurements.

## Battery Options

An AC power supply and two Sony "L" batteries for DC power are included in this incredible package.

## Barn doors Included

Ikan's reliable barn doors with intensifiers allow you to shape the light to suit your needs.

## Maximum Power Draw

These lights output a maximum power draw of 50-Watts at 120 volts, allowing you to plug it into any AC power.

## Incandescent Equivalent

The Mylo Daylight Half x 1 LED Light is equivalent to a 750-watt incandescent light.

## MW8 Fixture Specifications

Light Source	800 0.06 Watt LEDs
Head Type	Bi-Color 3200K-5600K
Lens	45°
Beam Angle	50°
Control/Dimming	Knob Control
Build Material	Heavy Duty Metal Construction
Cooling System	Passive Cooling
Yoke	Baby 5/8" & Junior 1-1/8" Combo Pin
Fixture Size	14 x 7 x 2 In.
Fixture Weight	6 lbs

## Power Specifications

Power Supply	Input: 100-240 VAC Output: 15VDC @5.0A
Fixture Power Consumption	24W; 7.4-14.8 VDC

## Shipping Specifications

Shipping Dimensions	24 x 22 x 18 in.
Shipping Weight	52 lbs

## What's Included

- 3 x Dual Charger with Power Supply
- 3 x Neutral Diffusion Filter
- 6 x Sony Style "L" Type Batteries
- 3 x Half x 1 Light Fixture
- 3 x Power Supply with Cable
- 3 x Yoke Mount
- 3 x Light Stands
- 1 x Light Bag
- 1 x Stand Bag

## Accessories

- CV600 Digital LED Light Meter with Exposure & Spectrometer
- CP-STND-V3 Compact Light Stand Version 3
- HD-STND Heavy Duty Light Stand
- KCP-703 Stage Clamp with 16mm Stud
- ROLLR-STND10 2-Stage Roller Stand 10' 6"
- SW-04 Safety Wire

