

# TELEPROMPTER MONITORS



12" - 17" Monitors Compatible with Ikan Teleprompters




## What's Included


- 1 x Teleprompter Monitor



## Monitor Ports



- BNC – AV Composite Input
- VGA – Video Graphics Array DE15 Connection
- HDMI – High-Definition Multimedia Interface Input Connection
- Power Port – 12-24v Input



- HDMI – Switch HDMI input
- VGA – Switch to VGA input
- AV – Switch to composite BNC input
- Flip – Toggle image flip  
(Can be set to horizontal, vertical, or both via menu)
- Up Arrow – Toggle up to adjust setting
- Menu – Access to monitor settings
- Down Arrow – Toggle down to adjust setting

## Monitor Menu Settings

### Video Config

- Contrast (White Level)
- Brightness (Black Level)
- Tint (Chroma Hue)
- Chroma (Chroma Saturation)
- Sharpness (Detail)
- RGB Setup – Manually configure RGB
- Return

### System Config

- Menu Duration – Set duration of how long menu stays on screen
- Video Ratio – Set screen aspect ratio 16:9 or 4:3 (4:3 is native resolution, 16:9 will create black bars)
- Flip-H – Assign toggle button to flip image horizontally
- Flip-V – Assign toggle button to flip image vertically
- Reset – Factory reset
- Return

### PC Setup (Only available for VGA)

- H-Position – Adjust horizontal position
- V-Position – Adjust vertical position
- Auto – Monitor automatically adjust position
- Return

### Exit

## How to set-up FLIP button feature:

1. Press MENU button
2. Navigate to SYSTEM CONFIG.
3. Navigate to FLIP-V or FLIP-H
4. Change FLIP-V and/or FLIP-H to "ON"
5. Exit MENU
6. The FLIP button should now be activated and can be pressed to mirror the image Horizontally or Vertically
7. When FLIP-H is ON, the image will flip Horizontally
8. When FLIP-V is ON, the image will flip Vertically
9. If both are ON, the FLIP button will toggle both Horizontal and Vertical flip

# Specifications

## PT3700-M

17" Teleprompter Monitor

Aspect Ratio	4:3
Brightness	300 cd/m2
Diagonal	17"
Input Signal	Composite BNC, VGA, HDMI
Input Voltage	DC 12v / 4A
Power Consumption	10 w
Product Weight	6 lbs
Product Dimensions	15.75" x 13" x 1"
Resolution	1280 x 1024
Shipping Weight	8 lbs
Shipping Dimensions	16.25" x 14.25" x 2"
Viewing Angle	160° (H) / 170° (V)
UPC	847983014415

## PT17-HB-V2

17" High-Bright Teleprompter Monitor (Version 2)

Aspect Ratio	4:3
Brightness	1000 cd/m2
Diagonal	17"
Input Signal	Composite BNC, VGA, HDMI
Input Voltage	DC 12v / 4A
Power Consumption	10 w
Product Weight	6 lbs
Product Dimensions	15.75" x 13" x 1"
Resolution	1280 x 1024
Shipping Weight	8 lbs
Shipping Dimensions	16.25" x 14.25" x 2"
Viewing Angle	160° (H) / 170° (V)
UPC	847983032785

## Supported Video Signals

### HDMI

720x480i & 720x480p @ 59.94, 60 Hz  
720x576i & 720x576p @ 50 Hz  
1280x720p @ 50, 59.94, 60 Hz  
1920x1080i @ 50, 59.94, 60 Hz  
1920x1080psf @ 24, 25, 29.97, 30 Hz  
1920x1080p @ 23.97, 24, 25, 29.94, 30, 50, 59.94, 60 Hz

## Supported Video Signals

### HDMI

720x480i & 720x480p @ 59.94, 60 Hz  
720x576i & 720x576p @ 50 Hz  
1280x720p @ 50, 59.94, 60 Hz  
1920x1080i @ 50, 59.94, 60 Hz  
1920x1080psf @ 24, 25, 29.97, 30 Hz  
1920x1080p @ 23.98, 24, 25, 29.97, 30, 50, 59.94, 60 Hz



## PT3100E-M

15" Teleprompter Monitor

Aspect Ratio	4:3
Brightness	300 cd/m2
Diagonal	15"
Input Signal	Composite BNC, VGA, HDMI
Input Voltage	DC 12v / 4A
Power Consumption	10 w
Product Weight	5 lbs
Product Dimensions	14.25" x 11.25" x 1"
Resolution	1280 x 1024
Shipping Weight	7 lbs
Shipping Dimensions	15" x 12" x 4"
Viewing Angle	160° (H) / 170° (V)
UPC	847983011377

## PT15-HB-V2

15" High Bright Teleprompter Monitor (Version 2)

Aspect Ratio	4:3
Brightness	1000 cd/m2
Diagonal	15"
Input Signal	Composite BNC, VGA, HDMI
Input Voltage	DC 12v / 4A
Power Consumption	10 w
Product Weight	5 lbs
Product Dimensions	14.25" x 11.25" x 1"
Resolution	1280 x 1024
Shipping Weight	7 lbs
Shipping Dimensions	15" x 12" x 4"
Viewing Angle	160° (H) / 170° (V)
UPC	847983032778

### Supported Video Signals

#### HDMI

720x480i & 720x480p @ 59.94, 60 Hz  
720x576i & 720x576p @ 50 Hz  
1280x720p @ 50, 59.94, 60 Hz  
1920x1080i @ 50, 59.94, 60 Hz  
1920x1080psf @ 24, 25, 29.97, 30 Hz  
1920x1080p @ 23.97, 24, 25, 29.94, 30, 50, 59.94, 60 Hz

### Supported Video Signals

#### HDMI

720x480i & 720x480p @ 59.94, 60 Hz  
720x576i & 720x576p @ 50 Hz  
1280x720p @ 50, 59.94, 60 Hz  
1920x1080i @ 50, 59.94, 60 Hz  
1920x1080psf @ 24, 25, 29.97, 30 Hz  
1920x1080p @ 23.97, 24, 25, 29.94, 30, 50, 59.94, 60 Hz

## PT1200-M

12" Teleprompter Monitor

Aspect Ratio	4:3
Brightness	350 cd/m2
Diagonal	12"
Input Signal	Composite BNC, VGA, HDMI
Input Voltage	DC 12v / 4A
Power Consumption	9 w
Weight	2 lb
Product Dimensions	12" x 10" x 1"
Resolution	1024 x 768
Viewing Angle	160° (H) / 170° (V)
Shipping Weight	3.76 lb
Shipping Dimensions	15" x 14" x 3"
UPC	847983015887

### Supported Video Signals

#### HDMI

720x480i & 720x480p @ 59.94, 60 Hz  
720x576i & 720x576p @ 50 Hz  
1280x720p @ 50, 59.94, 60 Hz  
1920x1080i @ 50, 59.94, 60 Hz  
1920x1080psf @ 24, 25, 29.97, 30 Hz  
1920x1080p @ 23.97, 24, 25, 29.94, 30, 50, 59.94, 60 Hz

## Learn More

More dynamic information at official website: [www.ikancorp.com](http://www.ikancorp.com)

## Support

Contact email: [support@ikancorp.com](mailto:support@ikancorp.com)

---

### CONDITIONS OF WARRANTY SERVICE

- Free service for one year from the day of purchase if the problem is caused by manufacturing errors.
- The components and maintenance service fee will be charged if the warranty period is expired.

#### **Free Service will not be Provided in the Following Situations:(\*Even if the product is still within the warranty period.)**

- Damage caused by abuse or misuse, dismantling, or changes to the product not made by the company.
- Damage caused by natural disaster, abnormal voltage, and environmental factors, etc.

©2021 Ikan International. All rights reserved.

