

Micro Array On-Camera Light

ONE SHEET

Overview

The Ikan iLED-MA Micro Flood Light is a small, yet powerful camera light with dimming control. The 21-1.2 Watt LEDs produce bright daylight 5600K at 120 degrees; suitable for fill light for small groups in low-lighting conditions. The unit is powered by a rechargable Li-lon battery via an included 5v mini USB cable.

The LEDs are covered by a frosted translucent plastic which provides effective diffusions at 120 degrees. In addition, the dimmer control can be set from 100% to 10% — perfect for those situations/events where your subjects do not want very bright lights in their eyes. The unit is small and fits in the palm of your hand to easily mount on your camera shoe. Yet, its sturdy design gives you the confidence you need when you are out in a demanding production environment.



iLED-MA | Micro Array On-Camera Light | UPC Code: 847983013159

Special Features

- Shoe Mount for Attaching to the Top of any Camera
- 120 Degrees Beam of Light
- Dimmable from 10-100%
- Internal Battery with Micro USB Charging

Recommended For

- Location Cinematography
- Location Photography



www.facebook.com/ikanseeit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp




www.youtube.com/ikancorp



www.ikancorp.com 1.713.27

1.713.272.8822 sales@ikancorp.com





Multiple Mounting Points

Created for the professional on-the-go, the shoe mount can be oriented either vertically or horizontally depending on the user's situation and needs.

Easy Set Up

The included diffuser attaches very easily with magnetic clips on the face of the light.

Compact Size

A a total size of roughly 4x3 inches, this compact light is easy to carry, easy to set up, and lightweight enough to be mounted and have little effect on the overall weight or your rig or camera.

Multi-Use

With both a Camera shoe mount and a ¼-20 threaded receiver, the user has the option to use this light mounted to either a DSLR or an industry standard rig.

What's Included

1 x Multi-Array Light 1 x 6" USB Cable

Optional Accessories

IK1-GTRBendable TripodMA2077 In. Articulating ArmMA21111 In. Articulating ArmCV600Digital LED Light Meter

| Specifications | |
|---------------------|----------------------|
| Beam Angle | 120° |
| Build Material | Heavy Duty Plastic |
| Control | Dimming Knob |
| Cooling System | Passive |
| Fixture Size | 3.25" x 2.25" x 1.5" |
| Fixture Weight | 4.8 oz |
| Focusing | N/A |
| Head Type | 5600K Daylight |
| Lens | N/A |
| Light Source | 21-1.2 watt |
| Mount | Camera Shoe Mount |
| Operating Volts | 5v |
| Operating Wattage | 2 watts |
| Power Supply | 5v @ 1A - USB Mini |
| Shipping Dimensions | 5" x 5" x 5" |
| Shippina Weiaht | 1 lb |





