

QUICK START GUIDE



What's Included

□ 1 x iLED-MS Light□ 1 x 6" USB Charging Cord





© 2015 ikan Corporation. All rights Reserved



- 1. Power charging port is located on the base of the light, directly about ON/OFF switch.
- 2. The barndoor attachment for this light is unique because of it's multiple types of "doors". There are two standard doors, one diffusion door, and one CTO (Color Temperature Orange). Not to mention how easy it is to remove and attach.
- 3. Cold Shoe mount allows for easy and secure set up.

Specifications	
Beam Angle	30° @ 3 ft
Build Material	Heavy Duty Plastic
Control	Dimming Knob
Cooling System	Passive
Fixture Size	5" x 2" x 2"
Fixture Weight	4.5 oz
Focusing	N/A
Head Type	5600K Daylight
Lens	30 degrees
Light Source	4 watt LED
Mount	Camera Shoe Mount
Operating Volts	5v
Operating Wattage	5 watts
Power Supply	5v @ 1A USB Mini
Shipping Dimensions	5" x 5" x 5"
Shipping Weight	1 lbs

www.ikancorp.com

Learn More

More dynamic information at official website: www.ikancorp.com

Support

Contact email: support@ikancorp.com

CONDITIONS OF WARRANTY SERVICE

- Free service for one year from the day of purchase if the problem is caused by manufacturing errors.
- The components and maintenance service fee will be charged if the warranty period is expired.

Free Service will not be Provided in the Following Situations: (*Even if the product is still within the warranty period.)

- Damage caused by abuse or misuse, dismantling, or changes to the product not made by the company.
- Damage caused by natural disaster, abnormal voltage, and environmental factors, etc.