

iLED6

iLED6 Zoom ENG LED Light

ONE SHEET

Overview

The iLED6 Zoom ENG LED Light is designed and built for professionals who want a versatile, high quality, and rugged LED light at an affordable price. The Daylight 6 3/4" x 2 3/4" LED fixture delivers field-tested reliability, solid construction, and all the features required for professional performance.

The iLED6's features include an energy efficient 5600K LED that can adjust from a 30 to 60-degree angle. A rotary knob allows you to easily adjust and control the dimmer from 0-100%. The iLED6 incorporates a rotating 4-leaf barn door system with two solid doors for spill control, one door with a diffusion gel, and another with a tungsten gel.

iLED6 lights are also available in different kit combinations, which include stands, bags, and other accessories.



iLED6 | iLED6 Focusable Portable Field LED Light | UPC Code: 847983008186

Special Features

- Lightweight on-camera light
- Barn doors with tungsten gel and diffusion gel
- Uses industry standard Sony L series batteries
- Adjust from spot to flood
- Easy to access rotary knob for dimming control

Recommended For

- On-Camera Lighting



www.facebook.com/ikanseit



www.twitter.com/ikancorp



www.vimeo.com/ikancorp



www.youtube.com/ikancorp

ikan

www.ikancorp.com

1.713.272.8822

sales@ikancorp.com

iLED6

Features you need, Prices you want.

Lightweight On-Camera Light

This lightweight on-camera light can be used in a variety of ways in any news or field production.

Barn Doors with Gels

The barn doors include two solid doors, one door with a tungsten filter, and another with a diffusion filter.

Uses Sony L Series Style Batteries

The Sony L batteries come standard with the iLED6 focusable light.

Adjust from Spot to Flood

The rubberized ring on the front allows you to change the light from spot to flood.

Rotary Knob for Dimming Control

The rubberized ring on the front allows you to change the light from spot to flood.

What's Included

- 1 x iLED6 Fixture
- 1 x AC Supply
- 1 x SM-301
- 1 x Sony L Battery
- 1 x Sony L Battery Charger

iLED6 Specifications

Beam Angle	Adjustable Degrees
Build Material	Molded Heavy Duty Plastic
Color Temperature	Daylight
Control	Local Knob Controls
Cooling System	Passive Heat Sink
Dimensions	7.33 x 2.65 x 2.65 in.
Dimming	10-100%
Fixture Size	6.75 x 2.25 x 2.75 in.
Fixture Weight	11 oz
Focusing	Yes
Head Type	Daylight
Lens	30°-60°
Light Source	1 80 watt LED 5600K
Mount	Ball Mount
Power Consumption	6W
Power Supply	12v @ 2amp
Rating	120V 60hz
Weight	2 lbs

Shipping Specifications

Shipping Dimensions	7 x 3 x 3 in.
Shipping Weight	4 lbs

Optional Accessories

- CP-STND-V3** Compact Light Stand Version 3
- ICH-DUAL-S** Dual Sony L Series Battery Compatible Charger
- IBS-970** Sony L-Series NP-F970 Compatible Battery
- IBS-750** Sony L-Series NP-F750 Compatible Battery
- AB101** Anton/Bauer Power Tap Cable with Coaxial

