

Lyra POE Bi-Color Studio Mini-Bowen LED Light w/ ArtNet and sACN DMX

The Ikan LBF60B-POE is a PoE-powered softbox light designed for professional studio, broadcast, and stage applications. Building on the foundation of its predecessor, it utilizes a single Ethernet (RJ45) cable for both power and DMX control, thanks to PoE++ compatibility. The light features a 11" mini Bowen mount softbox, providing soft, diffused illumination ideal for interview setups, product photography, and key lighting applications. (Patented)



Distance	FC	LUX
5600K		
5ft. / 1.5m	48.2	519
10ft. / 3m	9.71	105
15ft. / 4.5m	4.33	46.6
4400K		
5ft. / 1.5m	41.5	448
10ft. / 3m	9.07	97.6
15ft. / 4.5m	4.05	43.6
3200K		
5ft. / 1.5m	39.1	421
10ft. / 3m	9.21	99.2
15ft. / 4.5m	3.78	40.7

Physical Data	
Beam Angle	N/A
Fixture Dimensions	17 x 11 x 5.8 in. / 43.18 x 29.94 x 14.7 cm
Fixture Weight	2.7 lbs / 1.2 kg
Illumination Dimensions	11" Diameter
Mechanical Data	
Build Material	Heavy Duty Resin Plastic / Metal
Lens	Mini-Bowen Mount
Mounting	Yoke, Supports Standard Stage Clamps
Stand Use	Baby 5/8" & Junior 1-1/8" Combo Pin
Barn Doors	Removable
Electronical Data	
Power Input	110-220VAC
Operating Voltage	48VDC
Frequency	50/60 Hz
Max Power Consumption	60 W
Color Temperature	Bi-Color 2700K-6500K
Power Loss	Last Scene Hold
LED Type	CoB LED
CRI	97
TLCI	99
Power Supply	Input: 110-220VAC; Output: 48VDC @1.25A (Not Included)
Functionality	
Input/Output Ports	RJ45, USB Type C, Threaded Barrel Coaxial (Power)
DMX	ArtNet or sACN
Dimming Range	0 - 100%
Cooling	Passive
LED Lifetime	70,000 Hours
Display	LCD Screen
Environmental Data	
Operation Temperature	10 - 110 °F