


Lyra POE 1x2 Bi-Color Studio Panel Soft LED Light w/ ArtNet and sACN DMX

The Ikan LBX20-POE is an innovative 1x2 soft panel LED light that revolutionizes studio lighting with dual PoE++ ports for 170W power delivery and DMX control through Cat6 RJ45 Ethernet cables. This cutting-edge fixture seamlessly integrates into Q-SYS ecosystems via the Q-SYS Designer Plugin while supporting ArtNet and sACN protocols for comprehensive control options. (Patent Pending)



Distance	FC	LUX
5600K		
5ft. / 1.5m	209	2255
10ft. / 3m	57	618
15ft. / 4.5m	29	308
4400K		
5ft. / 1.5m	215	2327
10ft. / 3m	58	630
15ft. / 4.5m	29	318
3200K		
5ft. / 1.5m	187	2014
10ft. / 3m	51	549
15ft. / 4.5m	25	275

Physical Data	
Beam Angle	110 Degree
Fixture Dimensions	26 x 31 x 7 in. / 66.04 x 78.74 x 17.8 cm
Fixture Weight	25 lbs / 11.34 kg
Illumination Dimensions	12 x 24 in. / 31 x 61 cm
Mechanical Data	
Build Material	Heavy Duty Resin Plastic / Metal
Lens	1/2 Stop Soft Diffusion Panel
Mounting	30 Degree Angled Yoke, Supports Standard Stage Clamps
Stand Use	Baby 5/8" & Junior 1-1/8" Combo Pin w/ 90 Degree Offset
Barn Doors	Installed
Electronical Data	
Power Input	110-220VAC
Operating Voltage	48VDC
Frequency	50/60 Hz
Max Power Consumption	170 W
Color Temperature	Bi-Color 3200K-5600K
Power Loss	Last Scene Hold
LED Type	Chip LEDs
CRI	97
TLCI	99
Power Supply	Input: 100-240VAC; Output: 48VDC @5.2A 250W (Not Included)
Functionality	
Input/Output Ports	2 x RJ45, USB Type A, DMX512 In & Out (5 Pin), 3 Pin XLR (Power)
DMX	ArtNet, sACN, or DMX512 (5 Pin XLR)
Dimming Range	0 - 100%
Cooling	Passive
LED Lifetime	70,000 Hours
Display	LCD Screen
Environmental Data	
Operation Temperature	10 - 110 °F